

Client: BERNHARDT CONTRACTING LTD. 3540 Richmond Road Victoria, BC

Architect:
CASCADIA ARCHITECTS INC.
101 - 814 BROUGHTON ST.
VICTORIA, BC, V8W 1E4



DRAWING LIST:

FULL SIZE DRAWING LIST

DRAWINGS


—1535 Oak Crest Drive

	Cover
A0.1	Building Code, Site Information and Schedules
A1.0	Site Plan
A2.0	Lower Floor Plan
A2.1	Upper Floor Plan
A2.2	Roof Plan
A2.3	Foundation Plan
A3.0	Elevations
A3.1	Elevations
A4.0	Sections
A5.0	Window Details

OCTOBER 19, 2012 - CONSTRUCTION DRAWINGS BERNHARDT RESIDEN

CASCADIA ARCHITECTS

DAMANT + JOHANNKNECHT



PATIO DOOR

2'-6 x 7'-0 (2)

FBG/VNYL

FBG / VNYL DOOR WITH LITE

GENERAL NOTES:

Construction of a new single family home with secondary suite to meet requirements of existing RS-6 Zone.

REGULATORY REQUIREMENTS

1. Execute the Work in accordance with applicable bylaws, regulations, and building codes; conform to latest published revisions, addenda, supplementary and appropriate current standards presently recognized and enforced by authorities

2. All construction must conform with the following laws, regulations, codes, practices and standards, as replaced or amended

from time to time, unless specifically exempted on the Building Permit. • 2006 British Columbia Building Code.

• 2006 British Columbia Fire Code.

• 2006 British Columbia Plumbing Code.

• 2006 British Columbia Electrical Code Regulation. Should conflicts arise between one document or authority and another, obtain clarification from the Consultant before

proceeding with Work. The most stringent regulation will govern. 3. The Contractor shall submit for and obtain all necessary permits required to complete the Work as stipulated by Provincial and Municipal Authorities prior to the commencement of work.

4. Should hazardous materials be encountered, stop work and notify Consultant immediately. Do not proceed until written instructions have been received from Owner.

5. Comply with federal and provincial legislation, guidelines and codes of practice, including WorkSafeBC. DRAWINGS AND DOCUMENTS

6. These drawings shall be used in conjunction with the complete set of construction documents. The document components are not intended to identify contractual limits between Subcontractors, nor between the Contractor and his Subcontractors and the Contractor is responsible to coordinate and integrate the scope of work described in these component pieces. Refer to the architectural cover sheet for the complete list of consultants and drawings. Confirm document package with the Consultant

7. All dimensions are to gridlines, face of concrete, face of exterior sheathing, face of stud (interior walls), centerline of window/door R O. unless noted otherwise (u.n.o.) Contractor to verify all dimensions and confirm same on site. 8. Do not scale from drawings. Consultant to be contacted regarding any discrepancies prior to commencement of

9.All existing and new datums are geodetic (meters).

10. Provide a schedule of submittals at commencement of the project. Provide submittals listed for review with reasonable promptness and in an orderly sequence so as to not cause delay in the Work. Allow 10 working days for consultant review of shop drawings and submittals. Submittals shall be provided electronically. Each submittal shall be verified and coordinated with the requirements of the field conditions and the Contract Documents prior to submission to the consultants. Verify field

measurements and affected adjacent Work are coordinated. Do not commence Work affected by the submittal until review is complete.

FIRE-RATED ASSEMBL ES & FIRE STOPPING

11. Maintain the continuity of fire-rated assemblies whether or not shown on the Drawings. Continuity of fire-rated assemblies to be maintained where mechanical and electrical services penetrate fire separations. Fire-stop all penetrations using ULC listed Firestopping assemblies. Provide detailed product and assembly listings to the Consultant for review prior to installation. All firestopping to be concealed by finished surfaces to be reviewed by the Consultant prior to installation of finish surfaces. HRV design to meet 9.36 2.18 to prevent circulation of smoke between suites.

All ducts are to be non-combustible and serve only one fire compartment.

12. The Contractor shall coordinate hours of work and noisy activity to meet the bylaw requirements of the Municipality. Coordinate progress of the work, including progress schedules, submittals, use of site, utilities and construction closures with Municipal Authorities and with Owner's Representatives.

13. Maintain existing exits and life safety systems and provide proper and safe means of egress from all parts of the building and site to open spaces at all times to the approval of jurisdictional authorities.

MATERIAL AND EQUIPMENT STORAGE & INSTALLATION

14. Product and Material Quality: Defective products will be rejected, regardless of previous inspections. Inspection does not relieve responsibility, but is a precaution against oversight or error. Remove and replace defective products at own expense and be responsible for delays and expenses caused by rejection.

15. Storage, Handling and Protection: Handle and store products in a manner to prevent damage or soiling and in accordance with manufacturer's instructions when applicable. Store packaged or bundled products in original and undamaged condition with manufacturer's seals and labels intact. Unless otherwise indicated install products in accordance with manufacturer's instructions. Improper installation or erection of products, due to failure in complying with these requirements, authorizes the Consultant to require removal and reinstallation at no increase in Contract Price.

16. Hazardous Materials Information: Comply with requirements of Workplace Hazardous Materials Information System (WHMIS) regarding use, handling, storage, and disposal of hazardous materials; and regarding labeling and provision of material safety data sheets (MSDS) in accordance with jurisdictional authorities. Deliver copies of Material Safety Data Sheets (MSDS) to Owner on all products intended for use in the building.

CONSTRUCTION PRACTISES

17. t is the Owner / Contractor's responsibilty to have site soil conditions reviewed and advise the Consultant of any soil conditions which may require special foundation or footing design. All footings to bear on firm undisturbed soil or properly compacted fill, as verified by a geotechnical engineer licensed to practise in BC.

18. All wood framing to be SPF unless otherwise noted or engineered. All framing, lintels etc., are to be in accordance with the BC Building Code current edition, Part 9.

19. All structural elements shall be designed, reviewed and approved by an Engineer licensed to practice in the Province of BC. including but not limited to: subsurface bearing conditions, foundations and footings, formwork, spans, shear walls, pre-engineered components, beams, joists, lintels, columns and connections, window framing for wind loads, hand- and guardrail assemblies. The Contractor shall submit to the Consultant for review the Engineer's Letters of Assurance Schedule B and sealed drawings for these elements prior to ordering or installation on site construction. The Contractor will arrange and submit to the Architect the Engineer's Schedule C confirming field review these installed elements prior to requesting Substantial Completion or Occupancy.

20. Do not insulate framing or install vapour barriers and interior finishes on wood framing until the moisture content of the wood is below 19%. Use temporary heat or fans to facilitate drying as required. 21. Provide min. 200mm (8") clearance from grade to finish cladding materials. Concrete foundation walls shall extend min.

200mm (8") above grade. All wood in contact with concrete (ie sill plates) shall be separated by appropriate gasket material. Building water-shedding membrane (building -wrap or 2 layers 30min. building paper) shall be installed lapped and shingled to prevent water penetration of the envelope. Products shall conform to CAN/CGSB 51 32-m. 22. Stair treads shall be constructed of plywood or an engineered material, fastened with screws and sub-floor adhesive. All

floor sheathing shall be secured with 40mm (1 5/8") galv. floor screws at max. 6" oc. 23. All metal window, sill, and through-wall flashings shall slope to shed water away from the building envelope. Flashings over

openings shall extend min. 25mm (1") beyond opening width in each direction. 24. All openings into rain-screen or other ventilation cavities shall be protected with securely installed bug-screen material.

25. Windows shall meet the requirements of CAN/CGSB -12 and CSA A.400 for air- and water-tightness and security. Ratings shall be at a minimum A1, B3, C3. Windows within 2m of grade shall meet applicable F. These ratings shall be labelled on the windows in conformance with the standard requirements. Windows shall also meet the requits of the Provincial Energy Efficiency Act and shall be supplied with intact labels or submittal of calculations confirming conformance prior to installation. 26. Install hard-wired smoke detectors in accordance with BCBC Part 9 and not more than 5m from any bedroom door.

PROJECT WASTE MANAGEMENT

Maintain the Work in tidy condition, free from accumulation of waste products and debris. Employ processes that ensure the generation of as little waste to the landfill as possible. Be responsible to provide and pay for proper disposal and salvage of construction materials and waste on this project. Unless otherwise shown on the drawings, all salvaged materials become the Provide a location and facilities for separation of materials for waste or potential salvage and recycling. Recycled materials

may be collected together and sorted off-site.

Hazardous materials are to be separated, stored and disposed of in accordance with the requirements of the authorities having jurisdiction including the Provincial Waste Management Act and BC Special Waste Regulation.

Final Cleaning: Leave the Work broom clean before the inspection process commences. Clean and polish glass, hardware, stainless steel, chrome, porcelain enamel, baked enamel, plastic laminate, mechanical and electrical fixtures. Replace broken, scratched or disfigured glass. Remove stains, spots, marks and dirt from decorative Work, electrical and mechanical fixtures, furniture fitments and walls.

Vacuum clean and dust building interiors, inside millwork, behind grilles, louvres and screens. Damp mop floors in preparation Upon completion of the Work, submit to Owner red-line, hand-edited, Record Drawings of each sign in the Work of this

Submit manufacturer's maintenance instructions, and necessary tools to change signage.

WALL SCHEDULE

W1 - TYPICAL EXTERIOR WALL CONSTRUCTION

• 3/4" (19mm) SAND-FLOAT ACRYLIC FINISH STUCCO & METAL LATH on BACKERBOARD

• 3/4" (19mm) VERTICAL P.T. STRAPPING @ 200oc 1 LAYER SHEATHING MEMBRANE conforming to CAN/CGSB-51.32-M

• 3/4" (19mm) EXTERIOR PLYWOOD SHEATHING • 2" x 8" (38mm x 184mm) WOOD STUDS @ 2' (600mm) O.C. c/w

INSULATION (min RSI 5.28) • 1/2" (13mm) OSB AIR/VAPOUR RETARDER, all joints and penetrations sealed with approved A/B membrane tape

BATT INSULATION (min RSI 2.47) • 1 LAYER 1/2" (13mm) INTERIOR GWB FINISH

• 2" x 4" (38mm x 89mm) WOOD STUD FURRING @ 2' (600mm) O.C. c/w

W1a - GARAGE EXTERIOR WALL CONSTRUCTION • 3/4" (19mm) SAND-FLOAT ACRYLIC FINISH STUCCO & METAL LATH on BACKERBOARD • 3/4" (19mm) VERTICAL P.T. STRAPPING @ 200oc

• 1 LAYER SHEATHING MEMBRANE conforming to CAN/CGSB-51.32-M

• 3/4" (19mm) EXTERIOR PLYWOOD SHEATHING • 2" x 8" (38mm x 184mm) WOOD STUDS @ 2' (600mm) O.C. c/w INSULATION (min RSI 5.28)

• 1 LAYER 1/2" (13mm) INTERIOR GWB FINISH

W2 - INSULATED INTERIOR WALL 1 hr FR based on BCBC Appendix D Table 2.3.4.a and TABLE 2.3.4.C as permitted by 9.10.3.1

1 LAYER 5/8" (16mm) TYPE 'X' INTERIOR GWB FINISH • 2" x 8" (38mm x 184mm) WOOD STUDS @ 16" (400mm) O.C. c/w INSULATION (min RSI 5.28)

• 1/2" (13mm) OSB AIR/VAPOUR RETARDER, all joints and penetrations sealed with approved A/B membrane tape

• 2" x 4" (38mm x 89mm) WOOD STUD FURRING @ 2' (600mm) O.C. c/w BATT INSULATION (min RSI 2.47) • 1 LAYER 5/8" (16mm) TYPE 'X' INTERIOR GWB FINISH

W3a - FOUNDATION WALL • DRAINMAT PROTECTION BOARD

• RIGID EXPANDED POLYSTYRENE INSULATION (min RSI 7.35) full height of WATERPROOF MEMBRANE

• 8" (200mm) CONCRETE FOUNDATION WALL c/w STEEL RE-INFORCING as per Structural Engineering requirements. • 2" x 4" (38mm x 89mm) WOOD FURRING STUDS @ 2' (600mm) O.C. • 1 LAYER 1/2" (13mm) GWB

W3b - GARAGE FOUNDATION WALL • SELF-ADHERING WATERPROOF MEMBRANE • 8" (200mm) CONCRETE FOUNDATION WALL c/w STEEL RE-INFORCING

as per Structural Engineering requirements. **W4** - 1hr rated interior wall construction BCBC Table A-9.10.3.1 W1a

1 LAYER 5/8" (16mm) TYPE 'X' GWB • 2" x 4" (38mm x 89mm) WOOD STUDS @ 16" (400mm) O.C. with acoustic batt insulation • 1 LAYER 5/8" (16mm) TYPE 'X' GWB

W5 - TYPICAL INTERIOR WALL CONSTRUCTION • 1 LAYER 1/2" (13mm) GWB

• 2" x 4" (38mm x 89mm) WOOD STUDS @ 16" (400mm) O.C. with acoustic batt insulation • 1 LAYER 1/2" (13mm) GWB

SUBSTITUTE 1 LAYER 1/2" (13mm) MOISTURE RESISTANT GWB in BATHROOMS to height of 1.83m and up to & including ceilings over tubs

W6 - TYPICAL INTERIOR WALL CONSTRUCTION - PLUMBING WALL

• 1 LAYER 1/2" (13mm) GWB • 2" x 6" (38mm x 140mm) WOOD STUDS @ 16" (400mm) O.C. with acoustic batt insulation • 1 LAYER 1/2" (13mm) GWB

SUBSTITUTE 1 LAYER 1/2" (13mm) MOISTURE RESISTANT GWB in BATHROOMS to height of 1.83m and up to & including ceilings over tubs and showers

W6a - 1hr RATED INTERIOR WALL CONSTRUCTION - PLUMBING WALL derived from BCBC Table A-9.10.3.1 W1a 1 LAYER 5/8" (16mm) TYPE 'X' GWB • 2" x 6" (38mm x 140mm) WOOD STUDS @ 16" (400mm) O.C. with acoustic

batt insulation • 1 LAYER 5/8" (16mm) TYPE 'X' GWB

• 2" x 6" (38mm x 140mm) WOOD STUDS @ 2' (600mm) O.C.

SUBSTITUTE 1 LAYER 1/2" (13mm) DENS GLASS GOLD OR EQUIVALENT

W7 - FURRING WALL 1 LAYER 1/2" (13mm) GWB

BEHIND TUB ENCLOSURES AND SHOWERS

R1 - ROOF • 2 ply MODIFIED SBS ROOF MEMBRANE on

BATT INSULATION (min. RSI 9.8)

ROOF SCHEDULE

• 5/8" (16mm) ROOF SHEATHING • TAPERED WOOD STRAPPING PURLOINS in two layers and directions to achieve min. 1.5% slope to drains & cross ventilation of joist spaces. ROOF JOISTS (Refer to structural engineering for depth & spacing)

• 1/2" (13mm) OSB AIR/VAPOUR RETARDER, all joints and penetrations sealed with approved A/B membrane tape 2X4 (38X89) FURRING JOISTS @ 2' (600mm) O.C. c/w BATT INSULATION

(min RSI 2.47) • 1 LAYER 1/2" (13mm) GWB

FLOOR SCHEDULE

F1 - CONCRETE FLOOR SLAB FINISHED FLOOR

• 4" (100mm) RE-INFORCED CONCRETE SLAB ON GRADE • POLY VAPOUR RETARDER

• EPS RIGID INSULATION (min. RSI 7.5) • MIN. 6" (150mm) GRANULAR DRAINAGE LAYER UNDISTURBED NATIVE SOIL OR COMPACTED FILL (as approved by Geotechnical Engineer to suit loading)

F2 - SUSPENDED WOOD FLOOR ASSEMBLY; TABLE A-9.10.3.1.B FLOOR ASSEMBLY F8d FINISHED FLOOR

• 5/8" (16mm) PLYWOOD SUBFLOOR • MIN. 2" x 10" (38mm x 235mm) WOOD JOISTS or 241mm dp I-JOISTS @ 2' (600mm) MAX. O.C. C/W acoustic batt insulation • RESILIENT METAL CHANNELS @ 24" (600mm) O.C. • 1 LAYER 5/8" (16mm) TYPE 'X' GWB, staggered joints

F3 - SUSPENDED, INSULATED WOOD FLOOR ASSEMBLY OVER GARAGE • FINISHED FLOOR, based on TABLE A-9.10.3.1.B FLOOR ASSEMBLY F8d • 5/8" (16mm) PLYWOOD SUBFLOOR, all joints and penetrations

sealed with approved A/B membrane tape • MIN. 2" x 10" (38mm x 235mm) WOOD JOISTS or 241mm dp I-JOISTS @ 2' (600mm) MAX. O.C. C/W BATT INSULATION (min. RSI 9.8) • RESILIENT METAL CHANNELS @ 16" (400mm) O.C. • 2 LAYERS 5/8" (16mm) TYPE 'X' GWB

ZONING AND PROJECT INFORMATION:

PROPERTY LEGAL DESCRIPTION:

Lot A, (DD B45943), of Lot 14, Block 1, Section 36, Victoria District, Plan 7977

LOT AREA: 1748 m2

EXISTING LOT COVERAGE: 6.8% (118.77 m2)

PROPOSED LOT COVERAGE: 10.3% (180 m2)

MAIN FLOOR AREA: 180 m2

LOWER FLOOR AREA:

179 m2 (includes 49 m2 of garage)

GROSS FLOOR AREA: 359 m2

GARAGE FLOOR AREA:

BASEMENT FLOOR AREA: 72 m2

535.43 m2 (30.6% of Lot Area)

FLOOR SPACE RATIO:

HEIGHT OF BUILDING FROM AVERAGE GRADE:

TOTAL IMPERVIOUS SURFACE AREA:

SETBACKS:

Front Yard: 11.3m (6m required) 17.85m (7.5m required) Rear Yard: South 1.57m (1.5m min.) Side Yards:

North 6.85m Total 8.42 total (4.5m Required)

NUMBER OF STORIES:

Open Site Space:

Percentage Open Site:

OPEN SITE SPACE CALCULATION: 77.3% Building Area: 180 m2 Parking/Driveway: +188 m2 368 m2 Lot Area: 1748 m2 Building/Parking Area: <u>- 368 m2</u> Open Site Space: 1380 m2

1380 m2

<u>/ 1748 m2</u>

4 Construction Set 12.10.19 Building Permit revisions 12.09.05 12.08.29 window revisions issued for Building Permit 12.08.02

description date

CASCADIA ARCHITECTS 101 • 814 BROUGHTON STREET T 250.881.4841 VICTORIA B.C. V8W IE4 T 778.679.8739 www.cascadiaarchitects.ca F 250.519.0118

BUILDING CODE

PROJECT


Bernhardt Residence 1535 Oak Crest Drive, Victoria BC

Copyright reserved. This document and the designs described are, and at


all times, remain the property of Damant Architecture. t is to be used solely by the designated Client for purposes associated with the named Project and may not reproduced without written consent of the Architect.

not to scale MANT PROJECT NUMBER 12 10 19

HECKED BY



A0.1



Average Grade Calculation

46 67
47 49
47 64
45 13
44 91
+ 44 68


276 52


276 52 / 6 = 46 09 average grade

4	Construction Set	12.10.19
3	Building Permit revisions	12 09 05
	issued for Building Permit	12 08 02
2	Revised to meet RS 6	12 06 26
1	Landscape Changes	12 04 12
rev no	description	date

CASCADIA 101 • 814 BROUGHTON STREE VICTORIA B.C. V8W IE4 www.cascadiaarchitects	T 778.679.8739
TITLE	Site Plan
_	ernhardt Residence st Drive, Victoria BC
solely by the designated Client for	nd the designs described are, and at amant Architecture. t is to be used purposes associated with the named thout written consent of the Architect.
SCALE	as noted
DAMANT PROJECT NUMBER 1202	DATE 12 10 19
DRAWING FILE 1202 A1 0 Site Plan	CHECKED BY GD

A1.0







4	Construction Set	12.10.19
3	Building Permit revisions	12 09 05
2	ssued for building permit	12 08 02
1	Revised to meet RS 6	12 06 26
rev no	description	date

CASCADIA /	ARCHITECT
101 • 814 BROUGHTON STREE VICTORIA B.C. V8W IE4 www.cascadiaarchitects.	T 778.679.87
TITLE	
Lo	wer Floor Pla
PROJECT	
E	ernhardt Resider
1535 Oak Cre	st Drive, Victoria
Copyright reserved. This document a all times, remain the property of E solely by the designated Client for Project and may not reproduced wi	amant Architecture. t is to be purposes associated with the na
SCALE	
	as no
DAMANT PROJECT NUMBER 1202	DATE 12 10
DRAWING FILE 1202 A2 0 Plans vwx	CHECKED BY


A2.0






CASCADIA /	T 250.881.4841 T 778.679.8739
TITLE Up	per Floor Plan
_	Bernhardt Residence st Drive, Victoria BC
all times, remain the property of D solely by the designated Client for	and the designs described are, and at learn Architecture. It is to be used purposes associated with the named thout written consent of the Architect.
SCALE	as noted
DAMANT PROJECT NUMBER 1202	DATE 12 10 19
DRAWING FILE 1202 A2 0 Plans vwx	CHECKED BY GD
	REV.

A2.1





	Construction Set	12.10.19
	Building Permit revisions	12 09 05
	issued for building permit	12 08 02
rev no	description	date

CASCADIA ARCHITECTS

101 • 814 BROUGHTON STREET T 250.881.4841

VICTORIA B.C. V8W IE4 T 778.679.8739

www.cascadiaarchitects.ca F 250.519.0118

TITLE


Roof Plan

PROJECT

Bernhardt Residence 1535 Oak Crest Drive, Victoria BC

Copyright reserved. This document and the designs described are, and at all times, remain the property of Damant Architecture. t is to be used solely by the designated Client for purposes associated with the named Project and may not reproduced without written consent of the Architect.

SCALE	as noted
DAMANT PROJECT NUMBER 1202	DATE 12 10 19
DRAWING FILE 1202 Plans vwx	CHECKED BY GD
	REV.
	DWG. NO





		1
	Construction Set	12.10.19
	Building Permit revisions	12 09 05
	issued for building permit	12 08 02
rev no	description	date

CASCADIA ARCHITECTS

101 • 814 BROUGHTON STREET T 250.881.4841
VICTORIA B.C. V8W IE4 T 778.679.8739
www.cascadiaarchitects.ca F 250.519.0118

TITLE

Foundation Plan


PROJECT


Bernhardt Residence
1535 Oak Crest Drive, Victoria BC


Copyright reserved. This document and the designs described are, and at all times, remain the property of Damant Architecture. t is to be used solely by the designated Client for purposes associated with the named Project and may not reproduced without written consent of the Architect.


DAMANT PROJECT NUMBER
1202
DATE
1202
12 10 19
DRAWING FILE
1202 Plans vwx
GD
REV.

A2.3











1 Head detail - Tilt & Turn window

A5 0 Scale: Half Actual Size



Sill detail - Tilt & Turn window

Scale: Half Actual Size



Jamb detail - Tilt & Turn window

A5 0 Scale: Half Actual Size

8 CONT. FLEXIBLE EXT. GRADE
SEALANT & FOAM BACKER ROD

9 GYPSUM WALLBOARD

10 SELF-ADHERING A/B TAPE & SEALANT PROVIDE CONT. CONNECTION OF OSB
A/B LYR WITH WINDOW FRAME

11 OSB A/B LAYER

12 CONT. 1.5 X1.5 ALUM. SILL INSTALL
ANGLE

13 1 ENG. or SOLID STONE SILL

NOTE LEGEND

2 BUILDING WRAP

5 RIGID INSULATION


1 PRE-FIN. 22ga. METAL FLASHING

3 SELF-ADHERING W/P MEMBRANE (SAM)

4 CONT. FLEXIBLE EXT. GRADE SEALANT & FOAM BACKER ROD -FRONT AND BACK OF WINDOW FRAME

6 WINDOW REBATE FASTENER CLIP

7 WINDOW FRAME & GLAZING TO MEET PPHP PERFORMANCE REQU'TS.



A5.0